

# Technical Datasheet



Trade name : E-WELD Shield  
Reviewed: 09.09.2021  
Date of print : 09.09.2021

Page : 1 of 1

## Description

E-WELD Shield enables a clean, time- and cost effective work in the area of plasma and laser cutting. It effectively prevents larger slag clumping and allows easy slag removal. This ensures that the workpieces are in place on the bars at any time, which increases the quality of the cutting results. The service life of the bars is increased and thus the plant availability, as the cleaning and set-up time is considerably reduced.

## Chemical characterisation

Coating for plasma and laser cutting benches based on ceramic additives.

## Classification according to Regulation (EC) No.1272/2008 [CLP]

Aquatic Chronic 3 ; H412 - Hazardous to the aquatic environment : Category 3 ; Harmful to aquatic life with long lasting effects.

## Transport information

ADR : -

## Water hazard class (Classification according to AwSV)

Water hazard class : 2 (Obviously hazardous to water)

## Labelling for contents according to regulation (EC) No. 648/2004

-

## Safety equipment

Eye / Face protection:	suitable safety goggles acc. EN 166	In case of splash
Hand protection:	suitable gloves type EN 374	In case of possible or enduring skin contact
Respiratory protection:	Combination filtering device DIN EN 14387	not necessary

## Application

E-WELD Shield should be thoroughly mixed before use and applied to the new or cleaned crosspieces ideally twice. Drying time approx. 1 h. Remove the slag after approx. 4 weeks and apply a new sacrificial layer E-WELD Shield.

1 liter E-WELD Shield is sufficient for approx. 20 m<sup>2</sup>.

## Technical data

Appearance :	liquid		
Colour :	light grey		
Odour :	characteristic		
Boiling temperature :	> 100 °C	viscosity :	300 mPa*s
Flash point :	not applicable	Ignition temperature :	not available
Lower explosion limit :	not applicable	Upper explosion limit :	not applicable
Density (20 °C) :	ca. 1,4 g/cm <sup>3</sup>	pH-value :	7 - 8
VOC (EG) :	< 3 Wt %	VOC (CH) :	< 3 Wt %

## Storage

Keep container tightly closed. Keep/store only in original container. Protect against sub-zero temperatures. Optimized storage temperature is between 2 °C up to 35 °C. The product is storable in closed original packaging for at least 12 months. Starting date is the date of production.

Storage class (acc. TRGS 510): 12

## Disposal advices

The waste codes are recommendations based on the schedule use of this product. Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances.

<b>Waste code acc. EWC/AVV for unused product</b>	<b>Waste code acc. EWC/AVV for packaging</b>
08 02 03      Aqueous suspensions containing ceramic materials.	15 01 02      plastic packaging

Contaminated packaging must be emptied of all residues and, following appropriate cleaning, may be sent to a recycling plant. Uncleaned packaging must be disposed of in the same manner as the medium.

## Order information

**D01116**    10 kg Jerry Can