

Technical Datasheet



Trade name : E-NOX Care
Reviewed: 24.08.2022
Date of print : 02.05.2023

Page : 1 of 1

Description

E-NOX Care is a highly refined pure oil for the care and protection of stainless steel, aluminium and non ferrous metals. It leaves a slight shimmer film on the surface that protects against further contamination. Following fingerprints do not remain visible or can easily be removed with a cloth. Displaces moisture and protects against weather influences. Provides a long-term finish during indoor and outdoor storage.

Chemical characterisation

Highly refined protective and care oil. Contains surfactants and silicone oil.

Classification according to Regulation (EC) No.1272/2008 [CLP]

Eye Irrit. 2; H319 - Serious eye damage/eye irritation: Category 2A; Causes serious eye irritation.
Asp. Tox. 1 ; H304 - Aspiration hazard : Category 1 ; May be fatal if swallowed and enters airways.

Transport information

ADR : -

Water hazard class (Classification according to AwSV)

Water hazard class : 1 (Slightly hazardous to water)

Labelling for contents according to regulation (EC) No. 648/2004

-

Safety equipment

Eye / Face protection:	suitable safety goggles acc. EN 166	In case of splash
Hand protection:	suitable gloves type EN 374	In case of possible or enduring skin contact
Respiratory protection:	Combination filtering device DIN EN 14387	In case of exceeding exposure limit values

Application

E-NOX Care is ready-to-use. Just spray it on the surface or apply with a soft cloth. Wipe off excess product and polish the surface with a cloth.

Technical data

Appearance :	liquid		
Colour :	colourless		
Odour :	characteristic		
Boiling temperature :	Approx. 130 °C	Solidifying temperature :	not determined
Flash point :	not relevant	Ignition temperature :	not determined
Lower explosion limit :	not relevant	Upper explosion limit :	not relevant
Density (20 °C) :	Approx. 0,86 g/cm ³	pH-value :	not applicable
VOC (EG) :	0 Wt %	VOC (CH) :	33 Wt %

Storage

Keep container tightly closed. Keep/store only in original container. Protect against sub-zero temperatures. Optimized storage temperature is between 2 °C up to 35 °C. The product is storable in closed original packaging for at least 12 months. Starting date is the date of production.

Storage class (acc. TRGS 510): 10

Disposal advices

The waste codes are recommendations based on the schedule use of this product. Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances.

Waste code acc. EWC/AVV for unused product
07 06 99 wastes not otherwise specified.

Waste code acc. EWC/AVV for packaging
15 01 02 plastic packaging

The waste code for used product depends on the kind of contaminations that were washed from spare parts and may be different to those stated here.

Contaminated packaging must be emptied of all residues and, following appropriate cleaning, may be sent to a recycling plant. Uncleaned packaging must be disposed of in the same manner as the medium.

Order information

B50019 500 ml PET bottle with trigger – TU: 20 x 500 ml
B02019 20 l jerry can