

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Master Mould RL
Revision date : 20.03.2023
Print date : 28.06.2023

Version : 1.0.0

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Master Mould RL
Unique Formula Identifier : AV60-N0YY-U00V-REQW

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

PC 35 - Washing and cleaning products

1.3 Details of the supplier of the safety data sheet

Supplier

Bio-Circle Surface Technology GmbH

Street : Berensweg 200

Postal code/City : 33334 Gütersloh

Telephone : +49 5241 9443 0

Telefax : +49 5241 9443 44

Information contact : labor@bio-circle.de

1.4 Emergency telephone number

+49 5241 9443 51 during normal office hours
(Monday to Thursday from 8 am to 4 pm and Friday from 8 am to 3 pm)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Acute Tox. 4 ; H302 - Acute toxicity (oral) : Category 4 ; Harmful if swallowed.

Acute Tox. 4 ; H332 - Acute toxicity (inhalative) : Category 4 ; Harmful if inhaled.

Skin Irrit. 2 ; H315 - Skin corrosion/irritation : Category 2 ; Causes skin irritation.

Eye Dam. 1 ; H318 - Serious eye damage/eye irritation : Category 1 ; Causes serious eye damage.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Corrosion (GHS05) · Exclamation mark (GHS07)

Signal word

Danger

Hazard components for labelling

BENZYL ALCOHOL ; CAS No. : 100-51-6

FORMIC ACID 4 % ; CAS No. : 64-18-6

ISOTRIDECANOL, ETHOXYLATED (>= 2.5 EO) ; CAS No. : 69011-36-5

AMIDES, C8-18 (EVEN NUMBERED) AND C18 (UNSATD.), N,N-BIS(HYDROXYETHYL) ; CAS No. : 68155-07-7

Hazard statements

H318 Causes serious eye damage.

H302+H332 Harmful if swallowed or if inhaled.

H315 Causes skin irritation.

Precautionary statements

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Master Mould RL
Revision date : 20.03.2023
Print date : 28.06.2023

Version : 1.0.0

P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P332+P313 If skin irritation occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.
P301+P312 IF SWALLOWED: Call a POISON CENTER/doctor/.../ if you feel unwell.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P302+P352 IF ON SKIN: Wash with plenty of water/....

2.3 Other hazards

None

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous ingredients

BENZYL ALCOHOL ; REACH No. : 01-2119492630-38-XXXX ; EC No. : 202-859-9; CAS No. : 100-51-6

Weight fraction : $\geq 50 - < 100$ %

Classification 1272/2008 [CLP] : Acute Tox. 4 ; H302 Acute Tox. 4 ; H332 Eye Irrit. 2 ; H319

FORMIC ACID ; REACH No. : 01-2119491174-37-XXXX ; EC No. : 200-579-1; CAS No. : 64-18-6

Weight fraction : $\geq 2 - < 5$ %

Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 Met. Corr. 1 ; H290 Acute Tox. 3 ; H331 Skin Corr. 1A ; H314 Eye Dam. 1 ; H318 Acute Tox. 4 ; H302 EUH071
Substance with a common (EC) occupational exposure limit value.

Specific Conc. Limits : Skin Corr. 1A ; H314: C ≥ 90 % • Eye Dam. 1 ; H318: C ≥ 10 % • Skin Corr. 1B ; H314: C ≥ 10 % • Skin Corr. 1C ; H314: C ≥ 10 % • Eye Irrit. 2 ; H319: C ≥ 2 % • Skin Irrit. 2 ; H315: C ≥ 2 %

ISOTRIDECANOL, ETHOXYLATED (≥ 2.5 EO) ; REACH No. : (Polymer) ; EC No. : 931-138-8; CAS No. : 69011-36-5

Weight fraction : $\geq 1 - < 5$ %

Classification 1272/2008 [CLP] : Eye Dam. 1 ; H318 Acute Tox. 4 ; H302

Specific Conc. Limits : Eye Dam. 1 ; H318: C ≥ 10 %

AMIDES, C8-18 (EVEN NUMBERED) AND C18 (UNSATD.), N,N-BIS(HYDROXYETHYL) ; REACH No. : 01-2119490100-53-XXXX ; EC No. : 931-329-6; CAS No. : 68155-07-7

Weight fraction : $\geq 1 - < 2,5$ %

Classification 1272/2008 [CLP] : Eye Dam. 1 ; H318 Skin Irrit. 2 ; H315 Aquatic Chronic 2 ; H411

Additional information

For full text of Hazard- and EU Hazard-statements: see SECTION 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

When in doubt or if symptoms are observed, get medical advice. Never give anything by mouth to an unconscious person or a person with cramps.

Following inhalation

Remove casualty to fresh air and keep warm and at rest.

In case of skin contact

After contact with skin, wash immediately with plenty of water and soap. Rub greasy ointment into the skin.

After eye contact

Protect uninjured eye. In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Following ingestion

Rinse mouth thoroughly with water. Let 1 glass of water be drunken in little sips (dilution effect). Do NOT induce

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Master Mould RL
Revision date : 20.03.2023
Print date : 28.06.2023

Version : 1.0.0

vomiting. Call a physician immediately.

4.2 Most important symptoms and effects, both acute and delayed

Causes serious eye irritation. Causes skin irritation.

4.3 Indication of any immediate medical attention and special treatment needed

None

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water Foam Extinguishing powder Carbon dioxide (CO₂) Sand Nitrogen Extinguishing blanket

Unsuitable extinguishing media

Full water jet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

In case of fire may be liberated: Carbon monoxide , Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

5.4 Additional information

The product itself does not burn. Co-ordinate fire-fighting measures to the fire surroundings.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Special danger of slipping by leaking/spilling product.

6.2 Environmental precautions

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

6.3 Methods and material for containment and cleaning up

Clear spills immediately. Wipe up with absorbent material (eg. cloth, fleece). Wash with plenty of water. Treat the recovered material as prescribed in the section on waste disposal.

6.4 Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Keep container tightly closed.

7.2 Conditions for safe storage, including any incompatibilities

Keep/Store only in original container. Protect against : Frost .

Hints on joint storage

Storage class (TRGS 510) : 12

7.3 Specific end use(s)

Observe technical data sheet. Observe instructions for use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Trade name : Master Mould RL
Revision date : 20.03.2023
Print date : 28.06.2023

Version : 1.0.0

Occupational exposure limit values

BENZYL ALCOHOL ; CAS No. : 100-51-6

Limit value type (country of origin) : TRGS 900 (D)
Limit value : 5 ppm / 22 mg/m³
Peak limitation : 2(l)
Remark : H, Y
Version : 23.06.2022

FORMIC ACID ; CAS No. : 64-18-6

Limit value type (country of origin) : TRGS 900 (D)
Limit value : 5 ppm / 9,5 mg/m³
Peak limitation : 2(l)
Remark : Y
Version : 23.06.2022

Limit value type (country of origin) : TWA (EC)

Limit value : 5 ppm / 9 mg/m³
Version : 20.06.2019

DNEL-/PNEC-values

DNEL/DMEL

BENZYL ALCOHOL ; CAS No. : 100-51-6

Limit value type : DNEL worker (systemic)
Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : 90 mg/m³
Limit value type : DNEL worker (systemic)
Exposure route : Inhalation
Exposure frequency : Short-term
Limit value : 450 mg/m³
Limit value type : DNEL worker (systemic)
Exposure route : Dermal
Exposure frequency : Long-term
Limit value : 9,5 mg/kg
Limit value type : DNEL worker (systemic)
Exposure route : Dermal
Exposure frequency : Short-term
Limit value : 47 mg/kg

FORMIC ACID ; CAS No. : 64-18-6

Limit value type : DNEL worker (local)
Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : 9,5 mg/m³
Limit value type : DNEL worker (local)
Exposure route : Inhalation
Exposure frequency : Short-term
Limit value : 19 mg/m³

ISOTRIDECANOL, ETHOXYLATED (>= 2.5 EO) ; CAS No. : 69011-36-5

Limit value type : DNEL worker (systemic)
Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : 294 mg/m³
Limit value type : DNEL worker (systemic)
Exposure route : Dermal
Exposure frequency : Long-term
Limit value : 2080 mg/kg

AMIDES, C8-18 (EVEN NUMBERED) AND C18 (UNSATD.), N,N-BIS(HYDROXYETHYL) ; CAS No. : 68155-07-7

Limit value type : DNEL Consumer (local)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Master Mould RL
Revision date : 20.03.2023
Print date : 28.06.2023

Version : 1.0.0

Exposure route : Dermal
Exposure frequency : Long-term
Limit value : = 0,056 mg/cm²
Limit value type : DNEL Consumer (systemic)
Exposure route : Dermal
Exposure frequency : Long-term
Limit value : = 2,5 mg/kg
Assessment factor : 1 D
Limit value type : DNEL Consumer (systemic)
Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : = 21,73 mg/m³
Limit value type : DNEL Consumer (systemic)
Exposure route : Oral
Exposure frequency : Long-term
Limit value : = 6,25 mg/kg
Assessment factor : 1 D
Limit value type : DNEL worker (local)
Exposure route : Dermal
Exposure frequency : Long-term
Limit value : = 0,0936 mg/cm²
Limit value type : DNEL worker (systemic)
Exposure route : Dermal
Exposure frequency : Long-term
Limit value : = 4,16 mg/kg
Assessment factor : 1 D
Limit value type : DNEL worker (systemic)
Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : = 73,4 mg/m³

PNEC

AMIDES, C8-18 (EVEN NUMBERED) AND C18 (UNSATD.), N,N-BIS(HYDROXYETHYL) ; CAS No. : 68155-07-7

Limit value type : PNEC (Aquatic, freshwater)
Limit value : 0,007 mg/l
Limit value type : PNEC (Aquatic, intermittent release)
Limit value : 0,024 mg/l
Limit value type : PNEC (Aquatic, marine water)
Limit value : 0,0007 mg/l
Limit value type : PNEC (Sediment, freshwater)
Limit value : 0,195 mg/kg
Limit value type : PNEC (Sediment, marine water)
Limit value : 0,0195 mg/kg
Limit value type : PNEC (Soil)
Limit value : 0,0348 mg/kg
Limit value type : PNEC (Sewage treatment plant)
Limit value : 830 mg/l

8.2 Exposure controls

Personal protection equipment

Eye/face protection



Wear suitable safety goggles in case of splash.

Suitable eye protection

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Master Mould RL
Revision date : 20.03.2023
Print date : 28.06.2023

Version : 1.0.0

EN 166.

Skin protection

Hand protection



Suitable gloves type : EN 374.
Suitable material : NBR (Nitrile rubber)
Breakthrough time : 480 min.
Thickness of the glove material : 0.4 mm

Remark : The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Respiratory protection



Respiratory protection necessary at: exceeding exposure limit values

Suitable respiratory protection apparatus

Combination filtering device
Type : A

Remark

Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190).

General information

Do not put any product-impregnated cleaning rags into your trouser pockets. When using do not eat, drink, smoke, sniff. Avoid contact with skin, eyes and clothes. P362+P364 - Take off contaminated clothing and wash it before reuse. P264 - Wash hands thoroughly after handling.

8.3 Additional information

No tests have been performed. Selection made for preparations according to the best available knowledge and information on ingredients. In the case of preparations the resistance of glove materials cannot be calculated in advance so it has to be tested before use.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state : Liquid

Colour : colourless

Odour

characteristic

Safety characteristics

| | | | |
|--|--------------|---|----------------|
| Melting point/freezing point : | (1013 hPa) | | not determined |
| Initial boiling point and boiling range : | (1013 hPa) | > | 100 °C |
| Flash point : | | > | 85 °C |
| Auto-ignition temperature : | | | none |
| Flammability : | | | non-flammable |
| Lower explosion limit : | | | not relevant |
| Upper explosion limit : | | | not relevant |

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Master Mould RL
Revision date : 20.03.2023
Print date : 28.06.2023

Version : 1.0.0

| | | |
|-------------------------------------|---------------------|--------------------------------|
| Vapour pressure : | (50 °C) | not relevant |
| Density : | (20 °C) | 1,04 - 1,053 g/cm ³ |
| Solvent separation test : | (20 °C) | not relevant |
| Water solubility : | (20 °C) | partially soluble |
| pH : | (20 °C / 100 g/l) | 3 |
| Cinematic viscosity : | (20 °C) | < 30 mm ² /s |
| Relative vapour density : | (20 °C) | not determined |
| Maximum VOC content (EC) : | | 4,5 Weight-% |
| Maximum VOC content (Switzerland) : | | 93,6 Weight-% |
| Taxable VOC content (Switzerland) : | | 89,1 Weight-% |

9.2 Other information

No further relevant information available.

SECTION 10: Stability and reactivity

10.1 Reactivity

This material is considered to be non-reactive under normal use conditions.

10.2 Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

No information available.

10.5 Incompatible materials

No information available.

10.6 Hazardous decomposition products

No known hazardous decomposition products.
Decomposition products in case of fire: see section 5.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Harmful by inhalation and if swallowed.

Acute oral toxicity

| | |
|------------------|---|
| Parameter : | ATEmix |
| Exposure route : | Oral |
| Effective dose : | > 500 mg/m ³ |
| Parameter : | LD50 (BENZYL ALCOHOL ; CAS No. : 100-51-6) |
| Exposure route : | Oral |
| Species : | Rat |
| Effective dose : | 1230 - 1620 mg/kg |
| Parameter : | LD50 (FORMIC ACID ; CAS No. : 64-18-6) |
| Exposure route : | Oral |
| Species : | Rat |
| Effective dose : | 730 mg/kg |
| Method : | OECD 401 |
| Parameter : | LD50 (Amides, C8-18 (even numbered) and C18-unsatd., N,N-bis(hydroxyethyl) ; CAS No. : 8051-30-7) |
| Exposure route : | Oral |
| Species : | Rat |
| Effective dose : | > 5000 mg/kg |

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Master Mould RL
Revision date : 20.03.2023
Print date : 28.06.2023

Version : 1.0.0

Parameter : LD50 (ISOTRIDECANOL, ETHOXYLATED (>= 2.5 EO) ; CAS No. : 9043-30-5)
Exposure route : Oral
Species : Rat
Effective dose : 300 - 2000 mg/kg
Method : OECD 423

Acute dermal toxicity

Parameter : ATEmix
Exposure route : Dermal
Effective dose : > 2000 mg/kg
Parameter : LD50 (BENZYL ALCOHOL ; CAS No. : 100-51-6)
Exposure route : Dermal
Species : Rabbit
Effective dose : 2000 mg/kg
Parameter : LD50 (FORMIC ACID ; CAS No. : 64-18-6)
Exposure route : Dermal
Species : Rat
Effective dose : > 2000 mg/kg
Method : OECD 402
Parameter : LD50 (Amides, C8-18 (even numbered) and C18-unsatd., N,N-bis(hydroxyethyl) ; CAS No. : 8051-30-7)
Exposure route : Dermal
Species : Rabbit
Effective dose : > 2000 mg/kg
Parameter : LD50 (ISOTRIDECANOL, ETHOXYLATED (>= 2.5 EO) ; CAS No. : 9043-30-5)
Exposure route : Dermal
Species : Rabbit
Effective dose : > 2000 mg/kg
Method : OECD 402

Acute inhalation toxicity

Parameter : ATEmix
Exposure route : Inhalation (vapour)
Effective dose : > 10 mg/m³
Parameter : LC50 (BENZYL ALCOHOL ; CAS No. : 100-51-6)
Exposure route : Inhalation
Species : Rat
Effective dose : > 4178 mg/m³
Exposure time : 4 h
Method : OECD 403
Parameter : LC50 (BENZYL ALCOHOL ; CAS No. : 100-51-6)
Exposure route : Inhalation
Species : Rat
Effective dose : 1000 ppm
Exposure time : 8 h
Parameter : LC50 (FORMIC ACID ; CAS No. : 64-18-6)
Exposure route : Inhalation
Species : Rat
Effective dose : 7,4 mg/l
Exposure time : 4 h
Method : OECD 403

Corrosion

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitisation

Trade name : Master Mould RL
Revision date : 20.03.2023
Print date : 28.06.2023

Version : 1.0.0

Skin sensitisation

Parameter : Skin sensitisation (BENZYL ALCOHOL ; CAS No. : 100-51-6)

No further relevant information available.

Sensitisation to the respiratory tract

No further relevant information available.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Carcinogenicity

No further relevant information available.

Germ cell mutagenicity

No further relevant information available.

Reproductive toxicity

No further relevant information available.

STOT-single exposure

No further relevant information available.

STOT-repeated exposure

No further relevant information available.

Aspiration hazard

No further relevant information available.

11.2 Information on other hazards

Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

Toxicokinetics, metabolism and distribution

There are no data available on the preparation/mixture itself.

Other adverse effects

Has degreasing effect on the skin.

Additional information

Preparation not tested. The statement is derived from the properties of the single components.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity

Acute (short-term) fish toxicity

Parameter : LC50 (BENZYL ALCOHOL ; CAS No. : 100-51-6)

Species : Pimephales promelas (fathead minnow)

Evaluation parameter : Acute (short-term) fish toxicity

Effective dose : 460 mg/l

Exposure time : 96 h

Parameter : LC50 (FORMIC ACID ; CAS No. : 64-18-6)

Species : Danio rerio (zebrafish)

Evaluation parameter : Acute (short-term) fish toxicity

Effective dose : 130 mg/l

Exposure time : 96 h

Method : OECD 203

Parameter : LC50 (Amides, C8-18 (even numbered) and C18-unsatd., N,N-bis(hydroxyethyl) ; CAS No. : 8051-30-7)

Species : Fish

Evaluation parameter : Acute (short-term) fish toxicity

Effective dose : 2,4 mg/l

Exposure time : 96 h

Parameter : LC50 (ISOTRIDECANOL, ETHOXYLATED (>= 2.5 EO) ; CAS No. : 9043-30-5)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Master Mould RL
Revision date : 20.03.2023
Print date : 28.06.2023

Version : 1.0.0

Species : Cyprinus carpio (Common Carp)
Evaluation parameter : Acute (short-term) fish toxicity
Effective dose : > 1 mg/l
Exposure time : 96 h
Method : OECD 203

Chronic (long-term) fish toxicity

Parameter : NOEC (Amides, C8-18 (even numbered) and C18-unsatd., N,N-bis(hydroxyethyl) ; CAS No. : 8051-30-7)

Species : Fish
Evaluation parameter : Chronic (long-term) fish toxicity
Effective dose : 0,32 mg/l
Exposure time : 28 D
Method : OECD 204

Acute (short-term) toxicity to crustacea

Parameter : EC50 (BENZYL ALCOHOL ; CAS No. : 100-51-6)

Species : Daphnia magna (Big water flea)
Evaluation parameter : Acute (short-term) toxicity to crustacea
Effective dose : 230 mg/ml
Exposure time : 48 h
Method : OECD 202

Parameter : EC50 (FORMIC ACID ; CAS No. : 64-18-6)

Species : Daphnia magna (Big water flea)
Evaluation parameter : Acute (short-term) toxicity to crustacea
Effective dose : 365 mg/l
Exposure time : 48 h
Method : OECD 202

Parameter : NOEC (FORMIC ACID ; CAS No. : 64-18-6)

Species : Daphnia magna (Big water flea)
Evaluation parameter : Acute (short-term) toxicity to crustacea
Effective dose : 180 mg/l
Exposure time : 48 h
Method : OECD 202

Parameter : EC50 (Amides, C8-18 (even numbered) and C18-unsatd., N,N-bis(hydroxyethyl) ; CAS No. : 8051-30-7)

Species : Daphnia
Evaluation parameter : Acute (short-term) toxicity to crustacea
Effective dose : 3,2 mg/l
Exposure time : 48 h
Method : OECD 202

Parameter : EC50 (ISOTRIDECANOL, ETHOXYLATED (>= 2.5 EO) ; CAS No. : 9043-30-5)

Species : Daphnia magna (Big water flea)
Evaluation parameter : Acute (short-term) toxicity to crustacea
Effective dose : > 1 mg/l
Exposure time : 48 h
Method : OECD 202

Acute (short-term) toxicity to algae and cyanobacteria

Parameter : EC50 (BENZYL ALCOHOL ; CAS No. : 100-51-6)

Species : Pseudokirchneriella subcapitata
Evaluation parameter : Inhibition of growth rate
Effective dose : 770 mg/l
Exposure time : 72 h
Method : OECD 201

Parameter : EC50 (FORMIC ACID ; CAS No. : 64-18-6)

Species : Pseudokirchneriella subcapitata
Evaluation parameter : Acute (short-term) toxicity to algae and cyanobacteria
Effective dose : 1240 mg/l

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Master Mould RL
Revision date : 20.03.2023
Print date : 28.06.2023

Version : 1.0.0

Exposure time : 72 h
Method : OECD 201
Parameter : ErC50 (Amides, C8-18 (even numbered) and C18-unsatd., N,N-bis(hydroxyethyl) ; CAS No. : 8051-30-7)
Species : Algae
Evaluation parameter : Inhibition of growth rate
Effective dose : 18,6 mg/l
Exposure time : 72 h
Method : Regulation (EC) No. 440/2008, Annex C.3
Parameter : EC50 (ISOTRIDEKANOL, ETHOXYLATED (>= 2.5 EO) ; CAS No. : 9043-30-5)
Species : Desmodesmus subspicatus
Evaluation parameter : Acute (short-term) toxicity to algae and cyanobacteria
Effective dose : > 1 mg/l
Exposure time : 72 h
Method : OECD 201

Chronic (long-term) toxicity to aquatic algae and cyanobacteria

Parameter : NOEC (Amides, C8-18 (even numbered) and C18-unsatd., N,N-bis(hydroxyethyl) ; CAS No. : 8051-30-7)
Species : Algae
Evaluation parameter : Chronic (long-term) toxicity to aquatic algae and cyanobacteria
Effective dose : 2 mg/l
Exposure time : 72 h

Toxicity to microorganisms

Parameter : EC50 (BENZYL ALCOHOL ; CAS No. : 100-51-6)
Species : Toxicity to microorganisms
Effective dose : 2100 mg/l
Exposure time : 49 h
Parameter : EC50 (FORMIC ACID ; CAS No. : 64-18-6)
Species : Pseudomonas putida
Effective dose : 46,7 mg/l
Exposure time : 17 h
Parameter : EC50 (ISOTRIDEKANOL, ETHOXYLATED (>= 2.5 EO) ; CAS No. : 9043-30-5)
Species : Toxicity to microorganisms
Effective dose : > 140 mg/l

12.2 Persistence and degradability

Biodegradation

Parameter : Biodegradation (BENZYL ALCOHOL ; CAS No. : 100-51-6)
Inoculum : Biodegradation
Degradation rate : 95 - 97 %
Test duration : 21 D
Evaluation : Readily biodegradable (according to OECD criteria).
Method : OECD 301A
Parameter : DOC reduction (FORMIC ACID ; CAS No. : 64-18-6)
Inoculum : Biodegradation
Evaluation parameter : Aerobic
Degradation rate : 92 %
Test duration : 28 D
Method : OECD 301D
Parameter : Biodegradation (Amides, C8-18 (even numbered) and C18-unsatd., N,N-bis(hydroxyethyl) ; CAS No. : 8051-30-7)
Inoculum : Degree of elimination
Degradation rate : 92,5 %
Test duration : 28 D
Evaluation : Readily biodegradable (according to OECD criteria).
Method : OECD 301B
Parameter : Biodegradation (ISOTRIDEKANOL, ETHOXYLATED (>= 2.5 EO) ; CAS No. : 9043-30-

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Master Mould RL
Revision date : 20.03.2023
Print date : 28.06.2023

Version : 1.0.0

Inoculum : 5)
Degree of elimination
Evaluation parameter : Anaerobic
Degradation rate : > 60 %
Test duration : 60 D
Parameter : CO₂ formation (% of the theoretical value) (ISOTRIDEKANOL, ETHOXYLATED (>= 2.5 EO) ; CAS No. : 9043-30-5)
Inoculum : Degree of elimination
Evaluation parameter : Aerobic
Degradation rate : > 60 %
Test duration : 28 D
Evaluation : Readily biodegradable (according to OECD criteria).
Method : OECD 301B

12.3 Bioaccumulative potential

No indication of bioaccumulation potential.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6 Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7 Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Directive 2008/98/EC (Waste Framework Directive)

Before intended use

Waste codes/waste designations according to EWC/AVV

07 06 01* (Aqueous washing liquids and mother liquors)

20 01 29* (Detergents containing hazardous substances)

Other disposal recommendations

Dispose of waste according to applicable legislation. Dispose of contents/container to an appropriate recycling or disposal facility. Contaminated packages must be completely emptied and can be re-used following proper cleaning. Handle contaminated packages in the same way as the substance itself.

13.2 Additional information

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

SECTION 14: Transport information

14.1 UN number

No dangerous good in sense of these transport regulations.

14.2 UN proper shipping name

No dangerous good in sense of these transport regulations.

14.3 Transport hazard class(es)

No dangerous good in sense of these transport regulations.

14.4 Packing group

No dangerous good in sense of these transport regulations.

14.5 Environmental hazards

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Master Mould RL
Revision date : 20.03.2023
Print date : 28.06.2023

Version : 1.0.0

No dangerous good in sense of these transport regulations.

14.6 Special precautions for user

None

14.7 Maritime transport in bulk according to IMO instruments

No transport as bulk according to IBC Code.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Authorisations and/or restrictions on use

Restrictions on use

Use restriction according to REACH annex XVII, no. : 3, 40, 75

Other regulations (EU)

Labelling for contents according to regulation (EC) No. 648/2004

< 5 % amphoteric surfactants

< 5 % non-ionic surfactants

Contains the following substances: BENZYL ALCOHOL

National regulations

Restrictions of occupation

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Technische Anleitung zur Reinhaltung der Luft (TA-Luft)

Weight fraction (Number 5.2.5. I) : 5 - 10 %

Water hazard class

Classification according to AwSV - Class : 1 (Slightly hazardous to water)

15.2 Chemical Safety Assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

16.1 Indication of changes

None

16.2 Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (Europäisches Übereinkommen über die Beförderung gefährlicher Güter auf der Straße)

AOX: adsorbierbare organisch gebundene Halogene

AwSV: Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen

CAS: Chemical Abstracts Service (Unterabteilung der American Chemical Society)

CLP: Verordnung (EG) Nr. 1272/2008 über die Einstufung, Kennzeichnung und Verpackung von Stoffen und Gemischen (Classification Labelling and Packaging)

EAK / AVV: europäischer Abfallartenkatalog / Abfallverzeichnis-Verordnung

ECHA: Europäische Chemikalienagentur (European Chemicals Agency)

EINECS: : Altstoffverzeichnis (European Inventory of Existing Commercial Chemical Substances)

GHS: Global harmonisiertes System zur Einstufung und Kennzeichnung von Chemikalien (Globally Harmonized System of Classification and Labelling of Chemicals)

IATA: Internationale Luftverkehrs-Vereinigung (International Air Transport Association)

ICAO: Internationale Zivilluftfahrtorganisation (International Civil Aviation Organization)

IMDG: Gefahrgutkennzeichnung für gefährliche Güter im Seeschiffverkehr (International Maritime Code for Dangerous Goods)

RID: Regelung zur internationalen Beförderung gefährlicher Güter im Schienenverkehr (Règlement concernant le transport international ferroviaire de marchandises dangereuses)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Master Mould RL
Revision date : 20.03.2023
Print date : 28.06.2023

Version : 1.0.0

TRGS: Technische Regel für den Umgang mit Gefahrstoffen
VbF: Verordnung über brennbare Flüssigkeiten
VOC: flüchtige organische Verbindung (volatile organic compound)
VVEA: Verordnung über die Vermeidung und die Entsorgung von Abfällen
VwVwS: Verwaltungsvorschrift wassergefährdender Stoffe
WGK: Wassergefährdungsklasse

16.3 Key literature references and sources for data

DGUV: GESTIS-Stoffdatenbank
ECHA: Classification And Labelling Inventory
ECHA: Pre-registered Substances
ECHA: Registered Substances
EC Safety Data Sheet of Suppliers
ESIS: European Chemical Substances Information System
GDL: Gefahrstoffdatenbank der Länder
UBA Rigoletto: Wassergefährdende Stoffe
Regulation (EC) No. 1907/2006 of the European Parliament and of the Council
Regulation (EC) No. 1272/2008 of the European Parliament and of the Council

16.4 Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].
Evaluation :
Acute Toxicity (oral), Category 4 : Calculation method.
Acute Toxicity (inhalation), Category 4 : Calculation method.
Skin Irrit. 2 : Calculation method.
Eye Dam. 1 : Calculation method.

16.5 Relevant H- and EUH-phrases (Number and full text)

| | |
|--------|--|
| H226 | Flammable liquid and vapour. |
| H290 | May be corrosive to metals. |
| H302 | Harmful if swallowed. |
| H314 | Causes severe skin burns and eye damage. |
| H315 | Causes skin irritation. |
| H318 | Causes serious eye damage. |
| H319 | Causes serious eye irritation. |
| H331 | Toxic if inhaled. |
| H332 | Harmful if inhaled. |
| H411 | Toxic to aquatic life with long lasting effects. |
| EUH071 | Corrosive to the respiratory tract. |

16.6 Training advice

None

16.7 Additional information

None

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.