

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : UNO X
Revision date : 20.10.2023
Print date : 25.10.2023

Version (Revision) : 5.0.1 (4.2.3)

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

UNO X
Unique Formula Identifier : K910-S045-X00Q-R7UQ

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

PC 35 - Washing and cleaning products

Sectors of use [SU]

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Industrial uses

1.3 Details of the supplier of the safety data sheet

Supplier

Bio-Circle Surface Technology GmbH

Street : Berensweg 200

Postal code/City : 33334 Gütersloh

Telephone : +49 5241 9443 0

Telefax : +49 5241 9443 44

Information contact : labor@bio-circle.de

1.4 Emergency telephone number

+49 5241 9443 51 during normal office hours
(Monday to Thursday from 8 am to 4 pm and Friday from 8 am to 3 pm)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Met. Corr. 1 ; H290 - Corrosive to metals : Category 1 ; May be corrosive to metals.
Acute Tox. 4 ; H302 - Acute toxicity (oral) : Category 4 ; Harmful if swallowed.
Skin Corr. 1A ; H314 - Skin corrosion/irritation : Category 1A ; Causes severe skin burns and eye damage.
Eye Dam. 1 ; H318 - Serious eye damage/eye irritation : Category 1 ; Causes serious eye damage.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Corrosion (GHS05) · Exclamation mark (GHS07)

Signal word

Danger

Hazard components for labelling

POTASSIUM HYDROXIDE ; CAS No. : 1310-58-3
DISODIUM METASILICATE ; CAS No. : 6834-92-0

Hazard statements

H290 May be corrosive to metals.
H314 Causes severe skin burns and eye damage.
H302 Harmful if swallowed.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : UNO X
Revision date : 20.10.2023
Print date : 25.10.2023

Version (Revision) : 5.0.1 (4.2.3)

Precautionary statements

P234 Keep only in original packaging.
P260 Do not breathe mist/vapours/spray.
P280 Wear protective gloves and eye/face protection.
P301+P330+P331 IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P310 Immediately call a POISON CENTER/doctor/....
P390 Absorb spillage to prevent material damage.

2.3 Other hazards

None

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous ingredients

POTASSIUM HYDROXIDE ; REACH No. : 01-2119487136-33-XXXX ; EC No. : 215-181-3; CAS No. : 1310-58-3

Weight fraction : $\geq 10 - < 25 \%$
Classification 1272/2008 [CLP] : Met. Corr. 1 ; H290 Skin Corr. 1A ; H314 Eye Dam. 1 ; H318 Acute Tox. 4 ; H302
Specific Conc. Limits : Skin Corr. 1A ; H314: C $\geq 5 \%$ • Eye Dam. 1 ; H318: C $\geq 2 \%$ • Skin Corr. 1B ; H314:
C $\geq 2 \%$ • Skin Corr. 1C ; H314: C $\geq 2 \%$ • Eye Irrit. 2 ; H319: C $\geq 0,5 \%$ • Skin Irrit.
2 ; H315: C $\geq 0,5 \%$

(2-METHOXYMETHYLETHOXY)PROPANOL ; REACH No. : 01-2119450011-60-XXXX ; EC No. : 252-104-2; CAS No. : 34590-94-8

Weight fraction : $\geq 1 - < 5 \%$
Classification 1272/2008 [CLP] : Substance with a common (EC) occupational exposure limit value.

POTASSIUM CUMENESULFONATE ; REACH No. : 01-2119489427-24-XXXX ; EC No. : 629-764-9; CAS No. : 164524-02-1

Weight fraction : $\geq 1 - < 5 \%$
Classification 1272/2008 [CLP] : Eye Irrit. 2 ; H319

SODIUM CUMENESULPHONATE ; REACH No. : 01-2119489411-37-XXXX ; EC No. : 239-854-6; CAS No. : 15763-76-5

Weight fraction : $\geq 1 - < 5 \%$
Classification 1272/2008 [CLP] : Eye Irrit. 2 ; H319

D-GLUCOPYRANOSE, OLIGOMERIC, C8-10 GLYCOSIDES ; REACH No. : 01-2119488530-36-XXXX ; EC No. : 500-220-1;
CAS No. : 68515-73-1

Weight fraction : $\geq 1 - < 3 \%$
Classification 1272/2008 [CLP] : Eye Dam. 1 ; H318

DISODIUM METASILICATE ; REACH No. : 01-2119449811-37-XXXX ; EC No. : 229-912-9; CAS No. : 6834-92-0

Weight fraction : $\geq 1 - < 3 \%$
Classification 1272/2008 [CLP] : Skin Corr. 1B ; H314 Eye Dam. 1 ; H318 STOT SE 3 ; H335

ALANINE N,N-BIS(CARBOXYMETHYL), -TRINATRIUMSALT IN WATER ; REACH No. : 01-0000016977-53-XXXX ; CAS No. : 164462-16-2

Weight fraction : $\geq 1 - < 5 \%$
Classification 1272/2008 [CLP] : Met. Corr. 1 ; H290

Additional information

For full text of Hazard- and EU Hazard-statements: see SECTION 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : UNO X
Revision date : 20.10.2023
Print date : 25.10.2023

Version (Revision) : 5.0.1 (4.2.3)

General information

When in doubt or if symptoms are observed, get medical advice. Never give anything by mouth to an unconscious person or a person with cramps.

Following inhalation

Remove casualty to fresh air and keep warm and at rest.

In case of skin contact

After contact with skin, wash immediately with plenty of water and soap. Rub greasy ointment into the skin.

After eye contact

Protect uninjured eye. In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Following ingestion

Rinse mouth thoroughly with water. Let 1 glass of water be drunken in little sips (dilution effect). Do NOT induce vomiting. Call a physician immediately.

4.2 Most important symptoms and effects, both acute and delayed

Causes severe skin burns and eye damage.

4.3 Indication of any immediate medical attention and special treatment needed

None

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water Foam Extinguishing powder Carbon dioxide (CO₂) Sand Nitrogen Extinguishing blanket

Unsuitable extinguishing media

Full water jet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

In case of fire may be liberated: Carbon monoxide , Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

5.4 Additional information

The product itself does not burn. Co-ordinate fire-fighting measures to the fire surroundings. Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Special danger of slipping by leaking/spilling product.

6.2 Environmental precautions

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

6.3 Methods and material for containment and cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Clear spills immediately. Wipe up with absorbent material (eg. cloth, fleece). Wash with plenty of water. Treat the recovered material as prescribed in the section on waste disposal.

6.4 Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : UNO X
Revision date : 20.10.2023
Print date : 25.10.2023

Version (Revision) : 5.0.1 (4.2.3)

7.1 Precautions for safe handling

Keep container tightly closed. It is recommended to design all work processes always so that the following is excluded:
Inhalation of vapours or spray/mists

7.2 Conditions for safe storage, including any incompatibilities

Keep/Store only in original container. Protect against : Frost .

Hints on joint storage

Storage class (TRGS 510) : 8B

Do not store together with

Acid

7.3 Specific end use(s)

Observe technical data sheet. Observe instructions for use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

(2-METHOXYMETHYLETHOXY)PROPANOL ; CAS No. : 34590-94-8

Limit value type (country of origin) : TRGS 900 (D)

Limit value : 50 ppm / 310 mg/m³

Peak limitation : 1(l)

Version : 23.06.2022

Limit value type (country of origin) : TWA (EC)

Limit value : 50 ppm / 308 mg/m³

Remark : Skin

Version : 20.06.2019

DNEL-/PNEC-values

DNEL/DMEL

POTASSIUM HYDROXIDE ; CAS No. : 1310-58-3

Limit value type : DNEL Consumer (local)

Exposure route : Inhalation

Exposure frequency : Long-term

Limit value : 1 mg/m³

Limit value type : DNEL worker (local)

Exposure route : Inhalation

Exposure frequency : Long-term

Limit value : 1 mg/m³

(2-METHOXYMETHYLETHOXY)PROPANOL ; CAS No. : 34590-94-8

Limit value type : DNEL Consumer (systemic)

Exposure route : Inhalation

Exposure frequency : Long-term

Limit value : 37,2 mg/m³

Limit value type : DNEL Consumer (systemic)

Exposure route : Dermal

Exposure frequency : Long-term

Limit value : 121 mg/kg bw/day

Limit value type : DNEL Consumer (systemic)

Exposure route : Oral

Exposure frequency : Long-term

Limit value : 36 mg/kg

Limit value type : DNEL worker (systemic)

Exposure route : Inhalation

Exposure frequency : Long-term

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : UNO X
Revision date : 20.10.2023
Print date : 25.10.2023

Version (Revision) : 5.0.1 (4.2.3)

Limit value : 308 mg/m³
Limit value type : DNEL worker (systemic)
Exposure route : Dermal
Exposure frequency : Long-term
Limit value : 283 mg/kg bw/day
POTASSIUM CUMENESULFONATE ; CAS No. : 164524-02-1
Limit value type : DNEL Consumer (local)
Exposure route : Dermal
Exposure frequency : Long-term
Limit value : 0,048 mg/cm²
Limit value type : DNEL Consumer (systemic)
Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : 6,6 mg/m³
Limit value type : DNEL Consumer (systemic)
Exposure route : Dermal
Exposure frequency : Long-term
Limit value : 68,1 mg/kg bw/day
Limit value type : DNEL Consumer (systemic)
Exposure route : Oral
Exposure frequency : Long-term
Limit value : 3,8 mg/kg bw/day
Limit value type : DNEL worker (local)
Exposure route : Dermal
Exposure frequency : Long-term
Limit value : 0,096 mg/cm²
Limit value type : DNEL worker (systemic)
Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : 37,4 mg/m³
Limit value type : DNEL worker (systemic)
Exposure route : Dermal
Exposure frequency : Long-term
Limit value : 191 mg/kg bw/day
SODIUM CUMENESULPHONATE ; CAS No. : 15763-76-5
Limit value type : DNEL Consumer (local)
Exposure route : Dermal
Exposure frequency : Long-term
Limit value : 0,048 mg/cm²
Limit value type : DNEL Consumer (systemic)
Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : 6,6 mg/m³
Limit value type : DNEL Consumer (systemic)
Exposure route : Dermal
Exposure frequency : Long-term
Limit value : 68,1 mg/kg bw/day
Limit value type : DNEL Consumer (systemic)
Exposure route : Oral
Exposure frequency : Long-term
Limit value : 3,8 mg/kg bw/day
Limit value type : DNEL worker (local)
Exposure route : Dermal
Exposure frequency : Long-term
Limit value : 0,096 mg/cm²
Limit value type : DNEL worker (systemic)

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : UNO X
Revision date : 20.10.2023
Print date : 25.10.2023

Version (Revision) : 5.0.1 (4.2.3)

Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : 37,4 mg/m³
Limit value type : DNEL worker (systemic)
Exposure route : Dermal
Exposure frequency : Long-term
Limit value : 191 mg/kg bw/day
D-GLUCOPYRANOSE, OLIGOMERIC, C8-10 GLYCOSIDES ; CAS No. : 68515-73-1
Limit value type : DNEL Consumer (systemic)
Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : 124 mg/m³
Limit value type : DNEL Consumer (systemic)
Exposure route : Dermal
Exposure frequency : Long-term
Limit value : 357000 mg/kg bw/day
Limit value type : DNEL Consumer (systemic)
Exposure route : Oral
Exposure frequency : Long-term
Limit value : 35,7 mg/kg bw/day
Limit value type : DNEL worker (systemic)
Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : 420 mg/m³
Limit value type : DNEL worker (systemic)
Exposure route : Dermal
Exposure frequency : Long-term
Limit value : 595000 mg/kg bw/day
DISODIUM METASILICATE ; CAS No. : 6834-92-0
Limit value type : DNEL Consumer (systemic)
Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : 1,55 mg/m³
Limit value type : DNEL Consumer (systemic)
Exposure route : Dermal
Exposure frequency : Long-term
Limit value : 0,74 mg/kg bw/day
Limit value type : DNEL Consumer (systemic)
Exposure route : Oral
Exposure frequency : Long-term
Limit value : 0,74 mg/kg bw/day
Limit value type : DNEL worker (systemic)
Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : 6,22 mg/m³
Limit value type : DNEL worker (systemic)
Exposure route : Dermal
Exposure frequency : Long-term
Limit value : 1,49 mg/kg
ALANINE N,N-BIS(CARBOXYMETHYL), -TRINATRIUMSALT IN WATER ; CAS No. : 164462-16-2
Limit value type : DNEL Consumer (local)
Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : 2 mg/m³
Limit value type : DNEL Consumer (local and systemic)
Exposure route : Inhalation

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : UNO X
Revision date : 20.10.2023
Print date : 25.10.2023

Version (Revision) : 5.0.1 (4.2.3)

Exposure frequency : Short-term
Limit value : 20 mg/m³
Limit value type : DNEL Consumer (systemic)
Exposure route : Oral
Exposure frequency : Short-term
Limit value : 85 mg/kg bw/day
Limit value type : DNEL Consumer (systemic)
Exposure route : Oral
Exposure frequency : Long-term
Limit value : 17 mg/kg bw/day
Limit value type : DNEL Consumer (systemic)
Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : 20 mg/m³
Limit value type : DNEL worker (local)
Exposure route : Inhalation
Exposure frequency : Short-term
Limit value : 40 mg/m³
Limit value type : DNEL worker (local)
Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : 4 mg/m³
Limit value type : DNEL worker (systemic)
Exposure route : Inhalation
Exposure frequency : Short-term
Limit value : 40 mg/m³
Limit value type : DNEL worker (systemic)
Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : 40 mg/m³

PNEC

(2-METHOXYMETHYLETHOXY)PROPANOL ; CAS No. : 34590-94-8

Limit value type : PNEC (Aquatic, freshwater)
Limit value : 19 mg/l
Limit value type : PNEC (Aquatic, marine water)
Limit value : 1,9 mg/l
Limit value type : PNEC (Sediment, freshwater)
Limit value : 70,2 mg/kg
Limit value type : PNEC (Sediment, marine water)
Limit value : 7,02 mg/kg
Limit value type : PNEC (Soil)
Limit value : 2,74 mg/kg dw
Limit value type : PNEC (Sewage treatment plant)
Limit value : 4,168 mg/l

POTASSIUM CUMENESULFONATE ; CAS No. : 164524-02-1

Limit value type : PNEC (Aquatic, freshwater)
Limit value : 0,1 mg/l
Limit value type : PNEC (Aquatic, intermittent release)
Limit value : 1 mg/l
Limit value type : PNEC (Aquatic, marine water)
Limit value : 0,01 mg/l
Limit value type : PNEC (Sediment, freshwater)
Limit value : 0,372 mg/kg dw
Limit value type : PNEC (Sediment, marine water)
Limit value : 0,0372 mg/l
Limit value type : PNEC (Soil)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : UNO X
Revision date : 20.10.2023
Print date : 25.10.2023

Version (Revision) : 5.0.1 (4.2.3)

Limit value :	0,016 mg/kg dw
Limit value type :	PNEC (Sewage treatment plant)
Limit value :	100 mg/l
SODIUM CUMENESULPHONATE ; CAS No. : 15763-76-5	
Limit value type :	PNEC (Aquatic, freshwater)
Limit value :	0,1 mg/l
Limit value type :	PNEC (Aquatic, intermittent release)
Limit value :	1 mg/l
Limit value type :	PNEC (Aquatic, marine water)
Limit value :	0,01 mg/l
Limit value type :	PNEC (Sediment, freshwater)
Limit value :	0,372 mg/kg dw
Limit value type :	PNEC (Sediment, marine water)
Limit value :	0,0372 mg/kg dw
Limit value type :	PNEC (Soil)
Limit value :	0,016 mg/kg dw
Limit value type :	PNEC (Sewage treatment plant)
Limit value :	100 mg/l
D-GLUCOPYRANOSE, OLIGOMERIC, C8-10 GLYCOSIDES ; CAS No. : 68515-73-1	
Limit value type :	PNEC (Aquatic, freshwater)
Limit value :	0,176 mg/l
Limit value type :	PNEC (Aquatic, intermittent release)
Limit value :	0,27 mg/l
Limit value type :	PNEC (Aquatic, marine water)
Limit value :	0,0176 mg/l
Limit value type :	PNEC (Sediment, freshwater)
Limit value :	1,516 mg/kg dw
Limit value type :	PNEC (Sediment, marine water)
Limit value :	0,152 mg/kg dw
Limit value type :	PNEC (Soil)
Limit value :	0,654 mg/kg dw
Limit value type :	PNEC (Secondary poisoning)
Limit value :	111,11 mg/kg food
Limit value type :	PNEC (Sewage treatment plant)
Limit value :	560 mg/l
DISODIUM METASILICATE ; CAS No. : 6834-92-0	
Limit value type :	PNEC (Aquatic, freshwater)
Limit value :	7,5 mg/l
Limit value type :	PNEC (Aquatic, intermittent release)
Limit value :	7,5 mg/l
Limit value type :	PNEC (Aquatic, marine water)
Limit value :	1 mg/l
Limit value type :	PNEC (Sewage treatment plant)
Limit value :	1000 mg/l
ALANINE N,N-BIS(CARBOXYMETHYL), -TRINATRIUMSALT IN WATER ; CAS No. : 164462-16-2	
Limit value type :	PNEC (Aquatic, freshwater)
Limit value :	2 mg/l
Limit value type :	PNEC (Aquatic, marine water)
Limit value :	0,2 mg/l
Limit value type :	PNEC (Sediment, freshwater)
Limit value :	24 mg/kg dw
Limit value type :	PNEC Soil, Freshwater
Limit value :	2,5 mg/kg

8.2 Exposure controls

Personal protection equipment

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : UNO X
Revision date : 20.10.2023
Print date : 25.10.2023

Version (Revision) : 5.0.1 (4.2.3)

Eye/face protection



Wear suitable safety goggles in case of splash. In case of increased risk, additionally Face protection umbrella

Suitable eye protection
EN 166.

Skin protection

Hand protection



Suitable gloves type : EN 374.
Suitable material : NBR (Nitrile rubber)
Breakthrough time : 480 min.
Thickness of the glove material : 0.4 mm

Remark : The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Respiratory protection



Respiratory protection necessary at: exceeding exposure limit values

Suitable respiratory protection apparatus

Combination filtering device
Type : A P2

Remark

Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190).

General information

Do not put any product-impregnated cleaning rags into your trouser pockets. When using do not eat, drink, smoke, sniff. Avoid contact with skin, eyes and clothes. P362+P364 - Take off contaminated clothing and wash it before reuse. P264 - Wash hands thoroughly after handling.

8.3 Additional information

No tests have been performed. Selection made for preparations according to the best available knowledge and information on ingredients. In the case of preparations the resistance of glove materials cannot be calculated in advance so it has to be tested before use.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state : viscous
Colour : colourless

Odour

characteristic

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : UNO X
Revision date : 20.10.2023
Print date : 25.10.2023

Version (Revision) : 5.0.1 (4.2.3)

Safety characteristics

Melting point/freezing point :	(1013 hPa)		not determined	
Initial boiling point and boiling range :	(1013 hPa)	approx.	100 °C	
Flash point :			not relevant	DIN EN ISO 13736
Auto-ignition temperature :			none	
Flammability :			non-flammable	
Lower explosion limit :			not relevant	
Upper explosion limit :			not relevant	
Vapour pressure :	(20 °C)	<	24 hPa	Calculated
Density :	(20 °C)		1,142 g/cm ³	
Water solubility :	(20 °C)		completely miscible	
pH :	(20 °C)		14	
Cinematic viscosity :	(20 °C)	<	30 mm ² /s	
Relative vapour density :	(20 °C)		not determined	
Maximum VOC content (EC) :			1,5 Weight-%	
Maximum VOC content (Switzerland) :			1,5 Weight-%	
Taxable VOC content (Switzerland) :			1,5 Weight-%	
Corrosive to metals :			May be corrosive to metals.	

9.2 Other information

CH : This product is not under the liability for taxation of VOC acc. VOCV (<= 3 % VOC).

SECTION 10: Stability and reactivity

10.1 Reactivity

May be corrosive to metals.

10.2 Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

10.3 Possibility of hazardous reactions

May cause strong formation of hydrogen by contact with amphoteric metals (e.g. alumina, lead, zinc) - danger of explosion.

10.4 Conditions to avoid

No information available.

10.5 Incompatible materials

Exothermic reaction with: Acid

10.6 Hazardous decomposition products

No known hazardous decomposition products.
Decomposition products in case of fire: see section 5.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Acute oral toxicity

Parameter :	ATEmix
Exposure route :	Oral
Effective dose :	> 1500 mg/kg
Parameter :	LD50 (POTASSIUM HYDROXIDE ; CAS No. : 1310-58-3)
Exposure route :	Oral
Species :	Rat
Effective dose :	365 mg/kg
Method :	OECD 425

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : UNO X
Revision date : 20.10.2023
Print date : 25.10.2023

Version (Revision) : 5.0.1 (4.2.3)

Parameter : LD50 ((2-METHOXYMETHYLETHOXY)PROPANOL ; CAS No. : 34590-94-8)
Exposure route : Oral
Species : Rat
Effective dose : > 5000 mg/kg
Method : OECD 401
Parameter : LD50 (POTASSIUM CUMENESULFONATE ; CAS No. : 164524-02-1)
Exposure route : Oral
Species : Rat
Effective dose : > 7000 mg/kg
Method : OECD 401
Parameter : LD50 (SODIUM CUMENESULPHONATE ; CAS No. : 15763-76-5)
Exposure route : Oral
Species : Rat
Effective dose : > 7000 mg/kg
Method : OECD 401
Parameter : LD50 (D-GLUCOPYRANOSE, OLIGOMERIC, C8-10 GLYCOSIDES ; CAS No. : 68515-73-1)
Exposure route : Oral
Species : Rat
Effective dose : > 2000 mg/kg
Method : OECD 423
Parameter : LD50 (DISODIUM METASILICATE ; CAS No. : 6834-92-0)
Exposure route : Oral
Species : Mouse
Effective dose : 770 - 820 mg/kg
Parameter : LD50 (DISODIUM METASILICATE ; CAS No. : 6834-92-0)
Exposure route : Oral
Species : Rat
Effective dose : 1152 - 1349 mg/kg
Parameter : LD50 (ALANINE N,N-BIS(CARBOXYMETHYL), -TRINATRIUMSALT IN WATER ; CAS No. : 164462-16-2)
Exposure route : Oral
Species : Rat
Effective dose : > 4000 mg/kg

Acute dermal toxicity

Parameter : ATEmix
Exposure route : Dermal
Effective dose : > 2000 mg/kg
Parameter : LD50 ((2-METHOXYMETHYLETHOXY)PROPANOL ; CAS No. : 34590-94-8)
Exposure route : Dermal
Species : Rat
Effective dose : > 19020 mg/kg
Method : OECD 402
Parameter : LD50 (POTASSIUM CUMENESULFONATE ; CAS No. : 164524-02-1)
Exposure route : Dermal
Species : Rabbit
Effective dose : > 2000 mg/kg
Method : OECD 402
Parameter : LD50 (SODIUM CUMENESULPHONATE ; CAS No. : 15763-76-5)
Exposure route : Dermal
Species : Rat
Effective dose : > 2000 mg/kg
Method : OECD 402
Parameter : LD50 (D-GLUCOPYRANOSE, OLIGOMERIC, C8-10 GLYCOSIDES ; CAS No. : 68515-73-1)
Exposure route : Dermal

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : UNO X
Revision date : 20.10.2023
Print date : 25.10.2023

Version (Revision) : 5.0.1 (4.2.3)

Species : Rabbit
Effective dose : > 2000 mg/kg
Method : OECD 402
Parameter : LD50 (DISODIUM METASILICATE ; CAS No. : 6834-92-0)
Exposure route : Dermal
Species : Rat
Effective dose : > 5000 mg/kg
Parameter : LD50 (ALANINE N,N-BIS(CARBOXYMETHYL), -TRINATRIUMSALT IN WATER ; CAS No. : 164462-16-2)
Exposure route : Dermal
Species : Rat
Effective dose : > 4000 mg/kg
Method : OECD 402

Acute inhalation toxicity

Parameter : ATEmix
Exposure route : Inhalation (dust/mist)
Effective dose : > 5 mg/l
Parameter : LC0 ((2-METHOXYMETHYLETHOXY)PROPANOL ; CAS No. : 34590-94-8)
Exposure route : Inhalation
Species : Rat
Effective dose : > 275 ppm
Exposure time : 7 h
Method : OECD 403
Parameter : LC50 (POTASSIUM CUMENESULFONATE ; CAS No. : 164524-02-1)
Exposure route : Inhalation
Species : Rat
Effective dose : > 6,41 mg/l
Exposure time : 232 min
Method : OECD 403
Parameter : LC50 (SODIUM CUMENESULPHONATE ; CAS No. : 15763-76-5)
Exposure route : Inhalation
Species : Rat
Effective dose : > 6,41 mg/l
Exposure time : 232 min
Method : OECD 403
Parameter : LC50 (DISODIUM METASILICATE ; CAS No. : 6834-92-0)
Exposure route : Inhalation
Species : Rat
Effective dose : > 2,06 mg/l
Exposure time : 4 h
Parameter : LC50 (ALANINE N,N-BIS(CARBOXYMETHYL), -TRINATRIUMSALT IN WATER ; CAS No. : 164462-16-2)
Exposure route : Inhalation
Species : Rat
Effective dose : > 5 mg/l

Corrosion

Skin corrosion/irritation

Causes severe burns.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitisation

Skin sensitisation

No further relevant information available.

Sensitisation to the respiratory tract

No further relevant information available.

Trade name : UNO X
Revision date : 20.10.2023
Print date : 25.10.2023

Version (Revision) : 5.0.1 (4.2.3)

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Carcinogenicity

No further relevant information available.

Germ cell mutagenicity

No further relevant information available.

Reproductive toxicity

No further relevant information available.

STOT-single exposure

No further relevant information available.

STOT-repeated exposure

No further relevant information available.

Aspiration hazard

No further relevant information available.

11.2 Information on other hazards

Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

Toxicokinetics, metabolism and distribution

There are no data available on the preparation/mixture itself.

Other adverse effects

Has degreasing effect on the skin. May be absorbed through the skin. Causes poorly healing wounds.

Additional information

Preparation not tested. The statement is derived from the properties of the single components.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity

Acute (short-term) fish toxicity

Parameter :	LC50 (POTASSIUM HYDROXIDE ; CAS No. : 1310-58-3)
Species :	Fish
Evaluation parameter :	Acute (short-term) fish toxicity
Effective dose :	80 mg/l
Exposure time :	96 h
Parameter :	LC50 (ALANINE N,N-BIS(CARBOXYMETHYL), -TRINATRIUMSALT IN WATER ; CAS No. : 164462-16-2)
Species :	Danio rerio (zebrafish)
Evaluation parameter :	Acute (short-term) fish toxicity
Effective dose :	> 110 mg/l
Exposure time :	96 h
Method :	Regulation (EC) No. 440/2008, Annex C.1
Parameter :	LC50 ((2-METHOXYMETHYLETHOXY)PROPANOL ; CAS No. : 34590-94-8)
Species :	Poecilia reticulata (Guppy)
Evaluation parameter :	Acute (short-term) fish toxicity
Effective dose :	> 1000 mg/l
Exposure time :	96 h
Evaluation :	Harmless to fish up to the concentration tested.
Method :	OECD 203
Parameter :	LC50 (POTASSIUM CUMENESULFONATE ; CAS No. : 164524-02-1)
Species :	Cyprinus carpio (Common Carp)
Evaluation parameter :	Acute (short-term) fish toxicity
Effective dose :	> 100 mg/l

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : UNO X
Revision date : 20.10.2023
Print date : 25.10.2023

Version (Revision) : 5.0.1 (4.2.3)

Exposure time : 96 h
Parameter : LC50 (SODIUM CUMENESULPHONATE ; CAS No. : 15763-76-5)
Species : Cyprinus carpio (Common Carp)
Evaluation parameter : Acute (short-term) fish toxicity
Effective dose : > 100 mg/kg
Exposure time : 96 h
Parameter : LC50 (DISODIUM METASILICATE ; CAS No. : 6834-92-0)
Species : Fish
Evaluation parameter : Acute (short-term) fish toxicity
Effective dose : 2320 mg/l
Exposure time : 96 h

Chronic (long-term) fish toxicity

Parameter : NOEC (ALANINE N,N-BIS(CARBOXYMETHYL), -TRINATRIUMSALT IN WATER ; CAS No. : 164462-16-2)
Species : Oncorhynchus mykiss (Rainbow trout)
Evaluation parameter : Chronic (long-term) fish toxicity
Effective dose : = 100 mg/l
Exposure time : 28 D
Method : OECD 204

Acute (short-term) toxicity to crustacea

Parameter : EC50 (ALANINE N,N-BIS(CARBOXYMETHYL), -TRINATRIUMSALT IN WATER ; CAS No. : 164462-16-2)
Species : Daphnia magna (Big water flea)
Evaluation parameter : Acute (short-term) toxicity to crustacea
Effective dose : > 100 mg/l
Exposure time : 48 h
Method : Regulation (EC) No. 440/2008, Annex C.2
Parameter : EC50 ((2-METHOXYMETHYLETHOXY)PROPANOL ; CAS No. : 34590-94-8)
Species : Daphnia magna (Big water flea)
Evaluation parameter : Acute (short-term) daphnia toxicity
Effective dose : 1919 mg/l
Exposure time : 48 h
Evaluation : Harmless to daphnia up to the tested concentration.
Method : OECD 202

Parameter : EC50 (POTASSIUM CUMENESULFONATE ; CAS No. : 164524-02-1)
Species : Daphnia magna (Big water flea)
Evaluation parameter : Acute (short-term) toxicity to crustacea
Effective dose : > 100 mg/l
Exposure time : 48 h
Parameter : EC50 (SODIUM CUMENESULPHONATE ; CAS No. : 15763-76-5)
Species : Daphnia magna (Big water flea)
Evaluation parameter : Acute (short-term) toxicity to crustacea
Effective dose : > 100 mg/l
Exposure time : 48 h
Parameter : EC50 (DISODIUM METASILICATE ; CAS No. : 6834-92-0)
Species : Daphnia magna (Big water flea)
Evaluation parameter : Acute (short-term) toxicity to crustacea
Effective dose : 1700 mg/l
Exposure time : 48 h
Method : OECD 202

Acute (short-term) toxicity to algae and cyanobacteria

Parameter : EC50 (ALANINE N,N-BIS(CARBOXYMETHYL), -TRINATRIUMSALT IN WATER ; CAS No. : 164462-16-2)
Species : Scenedesmus subspicatus
Evaluation parameter : Acute (short-term) toxicity to algae and cyanobacteria
Effective dose : > 200 mg/l

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : UNO X
Revision date : 20.10.2023
Print date : 25.10.2023

Version (Revision) : 5.0.1 (4.2.3)

Exposure time : 72 h
Parameter : EC50 ((2-METHOXYMETHYLETHOXY)PROPANOL ; CAS No. : 34590-94-8)
Species : Pseudokirchneriella subcapitata
Evaluation parameter : Inhibition of growth rate
Effective dose : > 969 mg/l
Exposure time : 72 h
Evaluation : Harmless to algae up to the concentration tested.
Method : OECD 201
Parameter : EC50 (POTASSIUM CUMENESULFONATE ; CAS No. : 164524-02-1)
Species : Desmodesmus subspicatus
Evaluation parameter : Acute (short-term) toxicity to algae and cyanobacteria
Effective dose : > 100 mg/l
Exposure time : 72 h
Parameter : EC50 (SODIUM CUMENESULPHONATE ; CAS No. : 15763-76-5)
Species : Desmodesmus subspicatus
Evaluation parameter : Acute (short-term) toxicity to algae and cyanobacteria
Effective dose : > 100 mg/l
Exposure time : 72 h
Parameter : EC50 (DISODIUM METASILICATE ; CAS No. : 6834-92-0)
Species : Scenedesmus subspicatus
Evaluation parameter : Acute (short-term) toxicity to algae and cyanobacteria
Effective dose : 207 mg/l
Exposure time : 72 h
Method : DIN 38412 / part 9

Chronic (long-term) toxicity to aquatic algae and cyanobacteria

Parameter : NOEC ((2-METHOXYMETHYLETHOXY)PROPANOL ; CAS No. : 34590-94-8)
Species : Pseudokirchneriella subcapitata
Evaluation parameter : Inhibition of growth rate
Effective dose : 969 mg/l
Exposure time : 72 h
Evaluation : Harmless to algae up to the concentration tested.
Method : OECD 201

Toxicity to microorganisms

Parameter : EC10 ((2-METHOXYMETHYLETHOXY)PROPANOL ; CAS No. : 34590-94-8)
Species : Pseudomonas putida
Evaluation parameter : Bacteria toxicity
Effective dose : 4168 mg/l
Exposure time : 18 h
Parameter : EC50 (POTASSIUM CUMENESULFONATE ; CAS No. : 164524-02-1)
Species : Toxicity to microorganisms
Effective dose : > 1000 mg/l
Exposure time : 3 h
Parameter : EC50 (SODIUM CUMENESULPHONATE ; CAS No. : 15763-76-5)
Species : Toxicity to microorganisms
Effective dose : > 1000 mg/l
Parameter : EC50 (DISODIUM METASILICATE ; CAS No. : 6834-92-0)
Species : Toxicity to microorganisms
Effective dose : > 100 mg/l
Exposure time : 3 h

Sewage treatment plant

The product is an alkali. Before discharge into sewage plants the product normally needs to be neutralised.

12.2 Persistence and degradability

Biodegradation

Parameter : BOD (% of ThOD) (ALANINE N,N-BIS(CARBOXYMETHYL), -TRINATRIUMSALT IN WATER ; CAS No. : 164462-16-2)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : UNO X
Revision date : 20.10.2023
Print date : 25.10.2023

Version (Revision) : 5.0.1 (4.2.3)

Inoculum : Degree of elimination
Evaluation parameter : Aerobic
Degradation rate : > 80 - 90 %
Test duration : 28 D
Evaluation : Readily biodegradable (according to OECD criteria).
Method : OECD 301F
Parameter : DOC reduction (ALANINE N,N-BIS(CARBOXYMETHYL), -TRINATRIUMSALT IN WATER ; CAS No. : 164462-16-2)

Inoculum : Degree of elimination
Evaluation parameter : Aerobic
Degradation rate : > 90 - 100 %
Test duration : 28 D
Method : OECD 301F
Parameter : DOC reduction ((2-METHOXYMETHYLETHOXY)PROPANOL ; CAS No. : 34590-94-8)

Inoculum : Biodegradation
Evaluation parameter : Aerobic
Degradation rate : 96 %
Test duration : 28 D
Evaluation : Readily biodegradable (according to OECD criteria).
Method : OECD 301F
Parameter : Biodegradation (POTASSIUM CUMENESULFONATE ; CAS No. : 164524-02-1)

Inoculum : Biodegradation
Evaluation parameter : Aerobic
Degradation rate : 99,8 %
Test duration : 28 D
Evaluation : Readily biodegradable (according to OECD criteria).
Method : OECD 301B
Parameter : Biodegradation (SODIUM CUMENESULPHONATE ; CAS No. : 15763-76-5)

Inoculum : Biodegradation
Evaluation parameter : Aerobic
Degradation rate : 99,8 %
Test duration : 28 D
Evaluation : Readily biodegradable (according to OECD criteria).
Method : OECD 301B

12.3 Bioaccumulative potential

No indication of bioaccumulation potential.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6 Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7 Other adverse effects

No information available.

12.8 Additional ecotoxicological information

After neutralisation, reduction in toxic effects is observed.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Directive 2008/98/EC (Waste Framework Directive)

Before intended use

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : UNO X
Revision date : 20.10.2023
Print date : 25.10.2023

Version (Revision) : 5.0.1 (4.2.3)

Waste codes/waste designations according to EWC/AVV

07 06 01* (Aqueous washing liquids and mother liquors)
20 01 29* (Detergents containing hazardous substances)

Other disposal recommendations

Dispose of waste according to applicable legislation. Dispose of contents/ container to an approved waste disposal plant. Dispose of waste according to applicable legislation. Dispose of contents/container to an appropriate recycling or disposal facility. Contaminated packages must be completely emptied and can be re-used following proper cleaning. Handle contaminated packages in the same way as the substance itself.

13.2 Additional information

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

SECTION 14: Transport information

14.1 UN number

UN 3266

14.2 UN proper shipping name

Land transport (ADR/RID)

CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (POTASSIUM HYDROXIDE · DISODIUM TRIOXOSILICATE)

Sea transport (IMDG)

CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (POTASSIUM HYDROXIDE · DISODIUM TRIOXOSILICATE)

Air transport (ICAO-TI / IATA-DGR)

CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (POTASSIUM HYDROXIDE · DISODIUM TRIOXOSILICATE)

14.3 Transport hazard class(es)

Land transport (ADR/RID)

Class(es) : 8
Classification code : C5
Hazard identification number (Kemler No.) : 80
Tunnel restriction code : E
Special Provisions : LQ 11 · E 2
Hazard label(s) :



8

Sea transport (IMDG)

Class(es) : 8
EmS-No. : F-A / S-B
Special Provisions : LQ 11 · E 2 · IMDG-Code segregation group 18 - Alkalis
Hazard label(s) :



8

Air transport (ICAO-TI / IATA-DGR)

Class(es) : 8
Special Provisions : E 2
Hazard label(s) :



8

14.4 Packing group

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : UNO X
Revision date : 20.10.2023
Print date : 25.10.2023

Version (Revision) : 5.0.1 (4.2.3)

- II
- 14.5 Environmental hazards**
Land transport (ADR/RID) : No
Sea transport (IMDG) : No
Air transport (ICAO-TI / IATA-DGR) : No
- 14.6 Special precautions for user**
None
- 14.7 Maritime transport in bulk according to IMO instruments**
No transport as bulk according to IBC Code.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Authorisations and/or restrictions on use

Restrictions on use

Use restriction according to REACH annex XVII, no. : 3, 75

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Other regulations (EU)

Labelling for contents according to regulation (EC) No. 648/2004

< 5 % amphoteric surfactants

< 5 % anionic surfactants

< 5 % non-ionic surfactants

National regulations

Water hazard class

Classification according to AwSV - Class : 1 (Slightly hazardous to water)

15.2 Chemical Safety Assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

16.1 Indication of changes

01. Product identifier · 03. Hazardous ingredients · 08. Occupational exposure limit values · 08. DNEL/DMEL · 08. PNEC · 11. Endocrine disrupting properties · 12. Endocrine disrupting properties · 15. Restrictions on use · 15. Technische Anleitung zur Reinhaltung der Luft (TA-Luft)

16.2 Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (Europäisches Übereinkommen über die Beförderung gefährlicher Güter auf der Straße)

AOX: adsorbierbare organisch gebundene Halogene

AwSV: Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen

CAS: Chemical Abstracts Service (Unterabteilung der American Chemical Society)

CLP: Verordnung (EG) Nr. 1272/2008 über die Einstufung, Kennzeichnung und Verpackung von Stoffen und Gemischen (Classification Labelling and Packaging)

EAK / AVV: europäischer Abfallartenkatalog / Abfallverzeichnis-Verordnung

ECHA: Europäische Chemikalienagentur (European Chemicals Agency)

EINECS: : Altstoffverzeichnis (European Inventory of Existing Commercial Chemical Substances)

GHS: Global harmonisiertes System zur Einstufung und Kennzeichnung von Chemikalien (Globally Harmonized System of Classification and Labelling of Chemicals)

IATA: Internationale Luftverkehrs-Vereinigung (International Air Transport Association)

ICAO: Internationale Zivilluftfahrtorganisation (International Civil Aviation Organization)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : UNO X
Revision date : 20.10.2023
Print date : 25.10.2023

Version (Revision) : 5.0.1 (4.2.3)

IMDG: Gefahrgutkennzeichnung für gefährliche Güter im Seeschiffverkehr (International Maritime Code for Dangerous Goods)
RID: Regelung zur internationalen Beförderung gefährlicher Güter im Schienenverkehr (Règlement concernant le transport international ferroviaire de marchandises dangereuses)
TRGS: Technische Regel für den Umgang mit Gefahrstoffen
VbF: Verordnung über brennbare Flüssigkeiten
VOC: flüchtige organische Verbindung (volatile organic compound)
VVEA: Verordnung über die Vermeidung und die Entsorgung von Abfällen
VwVwS: Verwaltungsvorschrift wassergefährdender Stoffe
WGK: Wassergefährdungsklasse

16.3 Key literature references and sources for data

DGUV: GESTIS-Stoffdatenbank
ECHA: Classification And Labelling Inventory
ECHA: Pre-registered Substances
ECHA: Registered Substances
EC Safety Data Sheet of Suppliers
ESIS: European Chemical Substances Information System
GDL: Gefahrstoffdatenbank der Länder
UBA Rigoletto: Wassergefährdende Stoffe
Regulation (EC) No. 1907/2006 of the European Parliament and of the Council
|-> COMMISSION REGULATION (EU) 2020/878 of 18 June 2020
Regulation (EC) No. 1272/2008 of the European Parliament and of the Council

16.4 Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].
Evaluation
Met. Corr. 1 : UN Test, Part III of sub-section 37.4
Acute Tox. 4 : Calculation method.
Skin Corr. 1A : Calculation method.
Eye Dam. 1 : Calculation method.

16.5 Relevant H- and EUH-phrases (Number and full text)

H290	May be corrosive to metals.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.

16.6 Training advice

None

16.7 Additional information

None

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.